

WWW.PIPELINEEQUIPMENT.COM



FOAM PIGS



FABRICATION
EXTRUSION
MACHINE
COATING

PIPELINE EQUIPMENT, INC.
8403 S. 89TH WEST AVENUE
TULSA, OK 74131
PHONE: 918-224-4144
WWW.PIPELINEEQUIPMENT.COM



PEI OFFERS A FULL RANGE OF FOAM PIGS

PEI FOAM PIGS ARE OFFERED IN THREE DIFFERENT DENSITIES:

2-pound: light service

5-pound: medium service

8-pound: heavy service

Most PEI Foam Pigs are offered in sizes 2"-48".

The Foam Pig's core is made from an open-cell polyfoam then coated or sealed with a 90 Shore A durometer urethane coating.

FOAM PIGS ARE OFFERED IN MULTIPLE CONFIGURATIONS:

GRAY CRISS-CROSS: For light cleaning and displacement

GRAY SPIRAL BRISTLE: For cleaning

GRAY MULTI-DISC: For drying, cleaning, and displacement

BARE SWAB: For drying

GRAY CRISS-CROSS AND SPIRAL BRISTLE:

Features: Coated with a rigid 90 durometer urethane to toughen and prolong wear life. This pig can also be equipped with a spiral brush wrap to enhance the cleaning.

Application: To light clean or to remove debris and liquids. By adding the spiral brush, the cleaning ability is greatly improved.

GRAY MULTI-DISC:

Features: Multi-Disc which are reinforced with 90 durometer urethane.

Application: To line fill during hydro-test or to dewater after hydro-test. May also be used to dry or remove liquids.

GRAY BARE SWAB:

Features: May be flat nosed or taper nosed with sealed end to eliminate bypass.

Application: To dry pipeline following hydro-test or prove pipeline piggable.



FOAM PIGS